

33.2-inch Square LCD Display Specifications

Model: Y33SAD-A01

Version: V1.0

Document Number	Prepared by	Reviewed by	Approved by	Effective Date

Version	Description	Date	Fiction
V1.0	First Released	November 4, 2024	Chen Qingjie



Product Features

- ADSDS Panel Technology.
- New Appearance Design, No Tempered Glass.
- Uses high-resolution LCD panels to deliver clear, detailed, and realistic images and video effects.
- The rear shell is treated with high-temperature powder coating for wear resistance and corrosion protection.
- Supports multiple network connection options such as Ethernet and Wi-Fi.
- The motherboard uses the RK3288 quad-core application processor with a high clock speed of 1.9GHz for fast processing.
- Supports various playback modes such as automatic loop playback, full disk loop playback, single track loop playback, and more.
- Supports scheduled power on/off function
- Supports program update and upgrade directly via USB, making it easy and fast.
- Uses a durable aluminum alloy shell and other materials, offering good pressure resistance and shockproof performance, capable of adapting to various environments and reducing the risk of damage caused by collisions and vibrations.

Product Specifications

Display Specifications

Item	Parameter	Note
Display Specifications	Model	Y33SAD-A01
	LCD Tech	ADS
	Screen Size	33.2inch
	Resolution	1920x1920
	Brightness	500nits
	BLU	E-LED
	Contrast Ratio	1000:1
	Viewing Angle(H/V)	178°/178°
	Backlight Life	30,000 Hrs (Min)

Android System Configuration

Item	Parameter	Note
Android System Configuration	OS	Android 11.0
	CPU	Rockchip RK3568 Quad-core Cortex-A55,2.0GHz
	RAM	2GB
	ROM	32GB
	Network	LAN/Wi-Fi(2.4G/5G)/Wi-Fi 6/BT5.0
	I/O Interface	USB3.0*1 USB OTG*1 TF*1 SIM*1 Audio*1 RJ45*1 HDMI IN*1 DC IN*1

Physical

Item	Parameter	Note
Physical	Power supply	DC 12V*7A
	Power consumption	≤ 84W
	Bezel	7.68mm (L/RT/B)
	Body Dimension	615.36 (W) * 615.36 (H) * 25.1 (D) mm
	Set Weight	9.5Kg
	Package Dimension (1Pcs Inside)	830 (W) * 700 (H) * 100 (D) mm
	Package Weight (1Pcs Inside)	12Kg

Environmental Conditions

- ◆ Operating Temperature: 0°C~50°C
- ◆ Operating Humidity: 10%~80%RH
- ◆ Storage Temperature: -20°C~+60°C
- ◆ Storage Humidity: 10%~80%RH

Dimension drawing

